



CT-10

POWER. PERFORMANCE. STYLE.

SPECS

ENGINE	S&S Cycle T124 45-degree downdraft fuel-injected V-Twin
DISPLACEMENT	t124ci (2032cc)
DRIVETRAIN	Proprietary six-speed drivetrain with compact high-torque mainshaft and compact dry clutch
CHASSIS	Tubular steel frame with CNC-machined aluminium subframe; single-sided swingarm
FRONT SUSPENSION	Fully adjustable ARCH/Öhlins FGRT series fork
REAR SUSPENSION	Fully adjustable ARCH/Öhlins rear shock with reservoir and hydraulic pre-load adjustment
FRONT BRAKES	Dual ISR 6-piston monobloc radial mount calipers with ISR floating dampened discs
REAR BRAKES	Single ISR 4-piston monobloc radial mount caliper with ISR semi-floating disc
ABS	BOSCH
FRONT WHEEL	17" BST carbon fibre
REAR WHEEL	17" BST carbon fibre
FRONT TYRE	120/70-17 Michelin Power RS
REAR TYRE	240/45-17 Michelin Power RS
FOOT CONTROLS	Mid-mounted foot controls

Cytron Motorcycle Company LLC · 1-chōme-34-5 Hashiba, Taito City, Tokyo 111-0023, Japan · hello@cytroncycles.com
Every CT-10 is built to order; specification is indicative and confirmed in writing before build.